

Snazzi sun hood and transparent rain shield instructions



Fig. 1

The sun hood and rain shield are two separate items.

In order to fit the transparent rain shield, you must first fit the sun hood (see instructions below).

Fitting the sun hood:

The sun hood will arrive folded flat as shown (see Fig 2, right) There will be two thumb screws, one on either side of the hood (see Fig 3, below).



Fig. 2



Fig. 3

First loosen the thumb screws on either side of the hood.



Fig. 4

The hood fits into the frame adaptors, which are located under the slot in the top of the seat back cover (see Fig 4, left). Please note if your hood was ordered after the pushchair, the sun hood slot will need cutting. Simply cut through the middle of the slot using a Stanley knife, being careful not to cut beyond the stitched button-hole in the cover.

Open up the slot and feed the mounting clip into the frame adaptor, it may be easier to fit one side at a time. Push the clip into the adaptor until it locks in and will no longer pull out (please note that the padded cover can offer a bit of resistance, meaning it may be necessary to push firmly to get the clip to fully engage).



Fig. 5

Lift the front of the hood up so that it folds flat and sits in line with the backrest of the pushchair (see Fig 6, right).




Fig. 6




Fig. 7

Next lift up the back cover of the sun hood (see Fig 7, left), and fold it over the back of the pushchair backrest.

Fig 8: The back of the hood cover fitted over the pushchair backrest.




Fig. 8



Fig. 9

Finally pull the front of the hood down to the desired position (it may be helpful to hold the rear bar in place). Once set at the desired angle, tighten the 2 thumb screws. Each time you wish to change the angle of the hood, you must first loosen the thumb screws, adjust the angle as desired and then ensure that you tighten the screws to prevent them falling off.

To remove the sun hood, undo the top popper of the pushchair backrest cover as shown (see fig 10, right).



Fig. 10




Fig. 11

Then press in the locking clip and push up as shown (see Fig 11, left), this will release the sun hood from the frame. Do this for both sides then remove and fold the hood.

Fitting the rain shield:

With the sun hood in place and in the open position, place the rain shield over the top of the pushchair with the face flap to the front (the face flap has a single rectangular piece of Hook & loop in the middle, as circled- see Fig 12).

Pull the front of the cover down so that the elastic goes over the footrest as shown.



Fig. 12



Fig. 13

Next, open the rear flap, and feed the push handles through the flap. Fold down in between the push handles and secure with Hook & loop.

Hook the bottom back hooks onto the plastic bush on the rear frame of the pushchair as shown (see Fig 14, right).




Fig. 14




Fig. 15

Finally secure the front of the cover by wrapping the elastic strap around the footrest pole and hook back onto itself as shown (see Fig 15, left).

Important:

- When entering any building, ensure that you undo the Hook & loop flap at the front of the rain shield and fold it up so that the occupant of the pushchair does not over heat. If it is warm inside the building we would recommend removing the rain shield completely. Similarly if it is a hot day we would recommend that you leave this flap open if you have to use the rain shield to prevent overheating.
- We do not recommend that you ever leave your child unattended when using the pushchair. Special care should be taken when the sun hood and transparent rain shield are fitted to ensure the hood or rain shield are not too close to your child's face.
- When using the sun hood to protect your child from sunlight, we would recommend that this is used in conjunction with sun cream and appropriate clothing.
- Always ensure that your sun hood and rain shield are dry before you fold them for storage. Do not put either of these items near a heat source, such as fires, radiators and hairdryers as this will damage the material. Also, make sure you do not store the rain shield in direct sunlight as the heat may melt the adhesive. Both items can be wiped clean using a damp cloth.
- The sun hood and rain shield must be removed when folding the pushchair.
- The sun hood and rain shield must be removed when using the pushchair as a seat in a motor vehicle.
- The standard sun hood is made of showerproof black fabric. To protect the occupant from rain you must use the transparent rain shield in conjunction with the sun hood.
- If you remove the screws from the hood for any reason please ensure that you screw them back on to the hood through the hole in the fabric. Do not try to stretch the hole over the screw as you may damage the material.
- Always check that the thumb screws are tight to prevent them from falling off.