

 Tendercare Ltd, Unit 10, Minster Court, Littlehampton, West Sussex BN17 7RN Tel 01903 726161 Email: info@tendercareltd.com www.tendercareltd.com	SNAPPI® CHASSIS & INTERFACE  Snappi® Chassis; with swivelling front castors, gas strut operated tilt in space without fixed positions, height adjustable soft grip push handle and transit brackets fitted on forward facing model  Snappi® Interface; lightweight, easy to operate, quick release system with two stage safety catch.
Client Name: _____ Contact Name: _____ Address: _____ _____ _____ Telephone No: _____ E-mail: _____	

INFORMATION

Please supply the following information regarding the model and size of pushchair / wheelchair the seat will be used with. **Note: The Snappi Chassis & Interface complies with the requirements of ISO 7176-19 and is designed to be secured facing forward .When used with non Tendercare seats, you need to check suitability for transportation.**

SNAPPI® CHASSIS	SNAPPI® CHASSIS FACTORY FITTED UPGRADES																											
Snappi® Chassis - Size 1 SN7301 (Maximum carrying weight of seating system, occupant & all accessories 50kg)	Pneumatic Wheels - Upgrade SN6239 Front Locking castors - Upgrade SN6238 Push handle mounted attendant brakes - Hub* SN6259 * Standard foot operated brake is removed when this option is chosen. Not compatible with pneumatic wheels.																											
Snappi® Chassis - Size 2 SN7325 (Maximum carrying weight of seating system, occupant & all accessories 50kg)																												
SNAPPI® INTERFACE	FRAME ACCESSORIES																											
Snappi® Interface - Size 1 SN8215 Snappi® Interface - Size 2 SN8220	Frame Padding - Fits both sizes Wraparound SN6817 Infill Panel - forward facing only TSS0438																											
The Snappi® Interface is required for fitting special seating systems into the Snappi® Chassis. Not required when fitting CapsII seating system.																												
REARWARD FACING SNAPPI® CHASSIS	ACCESSORIES																											
Rearward Facing Snappi® Chassis - Size 1 SN6301 (Maximum carrying weight of seating system, occupant & all accessories 50kg). (Rearward facing model is not suitable for transportation and will not be supplied with any transit brackets fitted).	Sun/Rain Cover (incl. leg cover) - Fits to chassis SN6637/4 Transparent Rain Cover - Size 1 SN631 Transparent Rain Cover - Size 2 0SN6512 (Fits to chassis - cover has it's own framework) Rain Cover is only for use with forward-facing Snappi pushchairs.																											
	R/H Vertical Cylinder Carrier (recommended side)* TSS02 L/H Vertical Cylinder Carrier* TSS02 *Maximum 2 per chassis, Maximum O2 cylinder size of BOC CD or equivalent																											
TECHNICAL SPECIFICATION																												
	Equipment Carrying Tray* - Size 1 SN7306 Equipment Carrying Tray* with O2 cut out Size 1 SN7307 * Size 1 Internal Dimensions - 330mm (l) x 360mm (w) x 45mm (h) Equipment Carrying Tray* - Size 2 SN7328 Equipment Carrying Tray* with O2 cut out Size 2 SN7329 * Size 2 Internal Dimensions - 355mm (l) x 430mm (w) x 45mm (h) *Max Carrying Capacity 25kg																											
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th></th> <th>Size 1</th> <th>Size 2</th> </tr> </thead> <tbody> <tr> <td>Buggy (L x W x H) mm</td> <td>940 x 600 x 1010</td> <td>1030 x 675 x 1040</td> </tr> <tr> <td>Folded Buggy (L x W x H) mm</td> <td>865 x 600 x 400</td> <td>1030 x 675 x 400</td> </tr> <tr> <td>Seat Tilt (Forward Facing)</td> <td>0 - 40 degrees</td> <td>0 - 40 degrees</td> </tr> <tr> <td>Seat Tilt (Rearward Facing)</td> <td>8 - 48 degrees</td> <td>N/A</td> </tr> <tr> <td>Frame Colour</td> <td>Black</td> <td>Black</td> </tr> <tr> <td>Weight of Frame & Interface</td> <td>11.5kg</td> <td>12.5kg</td> </tr> <tr> <td>Max. Carrying Capacity*</td> <td>50kg</td> <td>50kg</td> </tr> <tr> <td>Max. Fitting Width</td> <td>350mm</td> <td>415mm</td> </tr> </tbody> </table>		Size 1	Size 2	Buggy (L x W x H) mm	940 x 600 x 1010	1030 x 675 x 1040	Folded Buggy (L x W x H) mm	865 x 600 x 400	1030 x 675 x 400	Seat Tilt (Forward Facing)	0 - 40 degrees	0 - 40 degrees	Seat Tilt (Rearward Facing)	8 - 48 degrees	N/A	Frame Colour	Black	Black	Weight of Frame & Interface	11.5kg	12.5kg	Max. Carrying Capacity*	50kg	50kg	Max. Fitting Width	350mm	415mm	Straps for Equipment Carrying Tray 77cm 1 x Pair TS6593 each(supplied loose with fixings to enable self fitting) 2 x Pairs TS6593 Shopping Basket - Size 1 SN7330 Maximum Carrying capacity 3kg Shopping Basket - Size 2 SN7331 Maximum Carrying capacity 3kg Sun Protection Parasol Style (UPF 50) Fits both sizes SN6334
	Size 1	Size 2																										
Buggy (L x W x H) mm	940 x 600 x 1010	1030 x 675 x 1040																										
Folded Buggy (L x W x H) mm	865 x 600 x 400	1030 x 675 x 400																										
Seat Tilt (Forward Facing)	0 - 40 degrees	0 - 40 degrees																										
Seat Tilt (Rearward Facing)	8 - 48 degrees	N/A																										
Frame Colour	Black	Black																										
Weight of Frame & Interface	11.5kg	12.5kg																										
Max. Carrying Capacity*	50kg	50kg																										
Max. Fitting Width	350mm	415mm																										
*Maximum carrying capacity includes seat unit, occupant and all																												

NOTES